

BT28BHRT

Modular Boom Series


SPECIFICATIONS

Size	Metric	British
Max. Working Height	28.50m	93ft 6in
Max. Platform Height	26.50m	86ft 11in
Max. Operating Range(+0.6m)	21.80m	71ft 6in
Max. Platform Range	21.20m	69ft 7in
Overall Length (Stowed) 🛕	11.60m	38ft 1in
Overall Length (Transport)	11.70m	38ft 5in
Overall Length (Transports: jib stowed)	8.75m	28ft 8in
Overall Width(Stowed) 😉	2.50m	8ft 2in
Overall Width (Transport)	2.28m	7ft 6in
Overall Height(Stowed) ©	2.87m	9ft 5in
Overall Height (Transport)	2.59m	8ft 6in
Platform Size(Length×Width)	2.44m×0.91m	8ft×3ft
Turntable Tailswing	1.61m	5ft 3in
Ground Clearance ①	0.41m	1ft 4in
Wheelbase (5)	2.80m	9ft 2in
Turning Radius(Inside/Outside)	1.87m/3.22m	6ft 2in/10ft 7in
Tyres	385/45-28	385/45-28

Performance		
S.W.L	454kg	1000lb
Max. Occupants	3	3
Gradeability	30%	30%
Travel Speed(Stowed)	6.0km/h	3.7mph
Travel Speed(Raised)	1.1km/h	0.7mph
Max. Working Slope	X-5°/Y-5°	X-5°/Y-5°
Turret Rotation	360°Continuous	360°Continuous
Platform Rotation	180°	180°
Jib Movement	135°	135°

Weight			
Overall Weight	18400kg	40565lb	

90\//420Ab	
80V/420Ah	80V/420Ah
12V	12V
54VAC/18kW	54VAC/18kW
Kubota Z482/9.8kW	Kubota Z482/9.8kW
110L	29gal
165L	43gal
	54VAC/18kW Kubota Z482/9.8kW 110L





BT28BHRT

Modular Boom Series

FEATURES

Standard Items

- 2.31m (7ft 7in) Jib
- Front Oscillating Axle
- Four-Wheel Steering
- Four-Wheel Drive
- Self-Leveling Platform
- 180° Left And Right Swing Platform
- Proportional Joystick Controls
- Thumb Rocker Steer
- Drive Enable
- Ac Power Cord To Platform
- Tilt Alarm
- Descent Alarm
- Flash
- Horn
- Hour Meter
- Integral Integrated Special Drive Axle For Construction Machinery
- 360° Continuous Turntable Rotation
- Positive Traction Four Wheel Drive
- Platform Load Sense System
- Fault Diagnosis System
- Operator Anti-crushing Protection System
- Harsh Environment Kits
- 12V DC Auxiliary Power
- Lithium Battery 80V/420Ah
- Driving Motor 18kW 3243rpm
- Lifting Motor 24kW 2150rpm



Boom-BT




Height-28m










Hybrid-Super Long Endurance Of 30 Days



454kg-Heavy Load



Multiple Steering Modes



Anti Extrusion Device