

SPECIFICATIONS

Size	Metric	British
Max. Working Height A	10.00m	32ft 10in
Max. Platform Height B	8.00m	26ft 3in
Overall Length(Without Outriggers) C	2.48m	8ft 2in
Overall Width D	0.83m	2ft 9in
Overall Height(Rails Up) E	2.36m	
Overall Height(Rails Down) F	2.00m	6ft 7in
Platform Size(Length×Width)	2.27m×0.81m	7ft 5in×2ft 8in
Platform Extension Size G	0.90m	2ft 11in
Ground Clearance(Stowed/Raised)	0.10m/0.019m	4in/1in
Wheelbase H	1.87m	6ft 2in
Turning Radius(Inside/Outside)	0m/2.10m	0/6ft 11in
Tyres	φ381×127mm	φ381×127mm




Performance		
S.W.L	230kg	507lb
S.W.L On Extension	113kg	249lb
Max. Occupants	2	2
Gradeability	25%	25%
Travel Speed(Stowed)	5.0km/h	3.10mph
Travel Speed(Raised)	0.8km/h	0.50mph
Max. Working Slope	X-1.5°/Y-3°	X-1.5°/Y-3°
Up/Down Speed	36/36sec	36/36sec

Weight		
Overall Weight(Lead-acid Battery)	2410kg	5313lb
Overall Weight(Lithium Battery)	2320kg	5115lb

Power		
Battery(Lead-acid Battery)	4×6V/185Ah	4×6V/185Ah
Battery(Lithium Battery)	24V/180Ah	24V/180Ah
Charger	24V/30A	24V/30A
Driving Motor	2×24V/0.87kW	2×24V/0.87kW
Lifting Motor	24V/3.20kW	24V/3.20kW



HYDRAULIC OIL FREE





JCPT1008PA

Oil-free & All-electric AWP Series

FEATURES

Standard Items

- Proportional Joystick Controls
- Self-Locking Gates
- One-Way Platform Extension Deck
- Drivable At Full Height
- Non-Marking Tyres
- Two-Wheel Drive
- Two-Wheel Steering
- Automatic Braking System
- Emergency Descent System
- Onboard Fault Diagnostic System
- Tilt Alarm
- Motion Alarm
- Horn
- Hour Meter
- Safety Arm For Troubleshooting
- Standard Transport Forklift Holes
- Charging Protection System
- Flashing LED Beacon
- Foldable Guard Rails
- Automatic Pothole Protection
- Drive Enable
- Charging Indicator
- Manual Brake Release
- Lanyard Attachment Point
- Tie-Down And Lifting Points
- Platform Load Sense System
- Emergency Stop Button

