

JCPT1912DCL

Self-propelled Scissor Lifts

SPECIFICATIONS

Size	Metric	British
Max. Working Height A	19.00m	62ft 4.0in
Max. Platform Height B	17.00m	55ft 9in
Overall Length C	3.76m	12ft 4in
Overall Width D	1.25m	4ft 1in
Overall Height(Rails Up) E	3.24m	10ft 8in
Overall Height(Rails Down) F	2.47m	8ft 1in
Platform Size(Length×Width)	3.44m×1.17m	11ft 3in × 3ft 10in
Platform Extension Size G	1.20m	3ft 11in
Ground Clearance(Stowed/Raised)	0.15m/0.025m	6in/1in
Wheelbase H	2.89m	9ft 6in
Turning Radius(Inside/Outside)	1.00m/3.50m	3ft 3in/11ft 6in
Tyres	22×9×16	22×9×16

Performance


S.W.L	500kg	1102lb
S.W.L On Extension	500kg	1102lb
Max. Occupants	2	2
Gradeability	30%	30%
Travel Speed(Stowed)	4.5km/h	2.80mph
Travel Speed(Raised)	0.4km/h	0.25mph
Max. Working Slope	X-1.5°/Y-3°	X-1.5°/Y-3°
Up/Down Speed	70/76sec	70/76sec

Weight

Overall Weight	7140kg	15741lb
----------------	--------	---------

Power

Hydraulic Tank	50L	13.2gal
Battery	48V/360Ah	48V/360Ah
Charger	48V/60A	48V/60A
Driving Motor	2×32VAC/3.3kW	2×32VAC/3.3kW
Lifting Motor	48VDC/12.0kW	48VDC/12.0kW



JCPT1912DCL

Self-propelled Scissor Lifts

FEATURES

Standard Items

- Proportional Joystick Controls
- Self-Locking Gates
- One-Way Platform Extension Deck
- Two-Wheel Drive
- Two-Wheel Steering
- Automatic Braking System
- Self-Weight Lowering System
- Tubing Explosion-Proof System
- Onboard Fault Diagnostic System
- Tilt Alarm
- Motion Alarm
- Horn
- Hour Meter
- Charging Protection System
- Flashing LED Beacon
- Foldable Guard Rails
- Drive Enable
- Charging Indicator
- Manual Brake Release
- Lanyard Attachment Point
- Tie-Down And Lifting Points
- Automatic Leveling Hydraulic Outriggers
- Emergency Pump
- Emergency Stop Button
- Platform Load Sense System
- Drivable At Full Height

